

Guide for the paste of touch foil(Permanent type)

背胶型操作指导书


1.Tools(工具)



2.The Introduction of the whole set of touch foil (整套触摸膜构成介绍)





3.The correct connection between FPC and e-board(甩尾与电路板正确连接展示)




4.The process of pasting touch film(贴膜过程详解)

1) Spread soap water to clean glass (往玻璃上喷洗洁净水并把玻璃清洗干净)



2) After the glass is cleaned fully, Spread the soap water to the glass again(玻璃被彻底清洗赶紧之后，再往玻璃上喷洗洁精水)



1、均匀喷洒溶液，用刮板将玻璃清洗干净，继续喷洒溶液；

3) Tear off the protective film from permanent type touch film. When you are tearing off, please spreading the soap water to the touch film(把背胶版触摸膜保护膜撕开，边撕边喷洗洁精水到触摸膜上)




2、揭掉触控膜背面保护层，边揭边喷溶液。切勿折、划伤膜体；




4) After the protective film is teared off,place touch film on the glass.(保护膜撕去后，将触摸膜放置在清洗后的玻璃上)






5) After Position the touch film perfectly, Spread the soap water to the glass(触摸膜位置选好后，往触摸膜上喷洗洁精水)



6) Use scraper to get rid of the soap water as long as fix the touch film as well



3、将膜平放在玻璃上，喷洒溶液，用刮板从中间向四周将溶液赶出：



3、将膜平放在玻璃上，喷洒溶液，用刮板从中间向四周将溶液赶出：

7)Connect the e-board and USB cable with FPC.Use dry rag or dishcloth to get the soap water completely and fully(把触摸膜甩尾与电路板及 USB 线连接起来,并用干抹布将洗洁精水彻底擦去)

